

J53230 SLP Satin 200

Coated Paper with SLP

Printability

- simplex printable

SLP (SOLVENT LATEX PRIMER)

RAW BASE PAPER FOR
PHOTOGRAPHIC APPLICATIONS



Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	204	± 7
Thickness	DIN EN ISO 534	µm	192	± 7
	DIN EN ISO 536	mil	7.6	± 0,28
Gloss BYK	ISO 2813	60°	16	± 5
Colour Elrepho UVO (D65)	ISO 2469	L	96,8	± 0,5
		a	0,2	± 0,3
		b	2,6	± 0,6
		delta b	12,2	± 0,8
CIE Whiteness (D65/10°) min.	ISO 2469		> 134	
Opacity min.	ISO 2469	%	> 91	

Printing Technology

-  Inkjet Solvent
-  Inkjet Latex
-  Inkjet UV

Certificates

- Certified for HP Latex Inks

Key Applications

- Sign & Display Graphics
- Advertising Posters
- Advertising posters for indoor and outdoor use
- Exhibition graphics
- POS signs

Benefits & Properties

- Optimum handling properties
- Excellent image quality with brilliant colours
- PVC free

Version: 09/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER