

FS-H90230 | SLP RC SATIN | 225

RESIN-COATED PAPER WITH SLP

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	226	± 7
Thickness DIN EN ISO 534	µm	213	± 7
	mil	8.4	± 0.27
Gloss BYK (60°) ISO 2813		22	± 5
Colour Elrepho UVO (D65) ISO 2469	L	93.7	± 0.6
	a	-0.3	± 0.4
	b	-1.6	± 0.6
	delta b	11.0	± 0.6
CIE whiteness (D65/10°) min. ISO 2469		> 142	
Opacity min. ISO 2469	%	> 94	

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

🔥 Inkjet solvent

💧 Inkjet latex

💜 Inkjet UV

Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers.

BENEFITS AND PROPERTIES

- › Pin-sharp details
- › Vivid colours
- › High colour consistency and gamut
- › Optimum handling properties
- › High light fastness
- › Outdoor durability
- › Outstanding lay-flat performance
- › Fast dry
- › PVC free

KEY APPLICATIONS

Sign & Display Graphics

- › POS signage
- › Exhibition graphics
- › Photo prints
- › Commercial posters for indoor and outdoor applications

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

www.dicavesa.com



Photo Classic
INKJET MEDIA