

MH 1886



Technical Data Sheet

Description	Print	Applications
MH 1886 is a premium matt coated inkjet papers. Available weights from 70 to 228 gsm.	universally printable with all common > dye inks > pigmented inks > latex inks	> designed for all full colour applications and photos > best for photorealistic printouts in premium-quality

Properties	Value	Unit	Test Method
Substance	183 ± 8	g/sqm	ISO 536
Thickness	245 ± 10	µm	ISO 534
Opacity	97 ± 3	%	ISO 2471
Stiffness md	48 ± 10	mN	ISO 2493
Stiffness cd	22 ± 5	mN	ISO 2493
Smoothness (fs)	> 8	sec	ISO 5627
CIE Whiteness (fs)	156 ± 6		ISO 11475
Shade (D65/10°) (fs) L*	97.0 ± 2		ISO 5631-2
a*	4.0 ± 1		ISO 5631-2
b*	-15.0 ± 2		ISO 5631-2

Availabilities	Certificates
Standard jumbo roll length	3 400 m
	> ISO 9001
	> ISO 14001
	> ISO 50001
	> FSC® Mix
	> PEFC™

Additional sizes and dimensions on request

Best printing results achieved in a standard climate of 23°C and 50% relative humidity. For problem-free running, always store the product in original packaging and protect it from direct sunlight and moisture. Before using our medium, check its suitability on your printer and for your planned application. We can assume no liability resulting from technical changes in printers and/or inks. Changes in the product design due to technical further developments will not be announced in advance.

www.dicavesa.com



Dark Matt

 INKJET MEDIA