

SL 2576

NFE170A



Technical Data Sheet

Description	Print	Applications
SL **76 is a range of microporous, resin coated photo papers with lustre surface. Available as SL 2076, SL 2576 and SL 2976.	universally printable with all common > dye inks > pigmented inks	> designed for high quality printouts on small format and large format printers, like photography, posters, signage etc.

Properties	Value	Unit	Test Method
Substance	255 ± 10	g/sqm	ISO 536
Thickness	265 ± 12	µm	ISO 534
Opacity	96 ± 3	%	ISO 2471
Stiffness md	65 ± 5	mN	ISO 2493
Stiffness cd	40 ± 5	mN	ISO 2493
Gloss value 60° (fs)	20 ± 4	%	ISO 2813
Smoothness (fs)	> 250	sec	ISO 5627
CIE Whiteness (fs)	136 ± 6		ISO 11475
Shade (D65/10°) (fs) L*	96.0 ± 2		ISO 5631-2
a*	1.5 ± 1		ISO 5631-2
b*	-10.5 ± 2		ISO 5631-2

Availabilities	Certificates
Standard jumbo roll	1534/1124 mm x 2300 m
	> ISO 9001
	> ISO 14001
	> ISO 50001

Best printing results achieved in a standard climate of 23°C and 50% relative humidity. For problem-free running, always store the product in original packaging and protect it from direct sunlight and moisture. Before using our medium, check its suitability on your printer and for your planned application. We can assume no liability resulting from technical changes in printers and/or inks. Changes in the product design due to technical further developments will not be announced in advance.

www.dicavesa.com

