

WINDOWS PERFORADO

Specification	Description	
PVC	Type	Calendered monomeric soft PVC film
	Thickness	180±10um
	Color Code	White
	Back	Black coating
	Shrinkage	≅ 0.8%
	Surface Tension	≅ 30dn/cm
	Opacity	>99%
	Holes No.	Average 130 per square inch
	Hole Diameter	1.6mm
	Distance Between Holes	2.4mm
	Hole Space	40%
Adhesive	Type	Clear solvent based removable pressure sensitive glue
	Weight(g/m ²)	25±2 g/m ²
	Adhesion Temperature	15°C~40°C
	180°Peeling Force	≅ 6N/25mm (FTM1)
	Initial Tack	≅ 3N/25MM*25MM (FTM9)
	Holding Power	≅ 1440min (FTM8)
	Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%
Liner	Type	Laminated Kraft paper
	Color	White
	Weight	195g±5g/m ²
	Release Force	0.05~0.2N/25MM
Storage Period	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%	
Application	It used in digital and silk screen printing machines for signage display, vehicle graphics, subway and glass walls of building	
Compatibility of machines and ink	Media is suitable for all UV, Solvent and Eco solvent digital printers with heating system. Inks should be the original inks from the printer manufacturers. The best printing temperature is 38-43°C.	