

BLACK BACK DISPLAY FABRIC

F004-2F



SPECIFICATIONS	METRIC	TEST METHOD	FEATURES	APPLICATIONS
Material	100% Polyester	DIN 60001, ASTM D7641	<ul style="list-style-type: none"> * No curling edge * Crease free * No fraying * Good flatness * High opaque 	<ul style="list-style-type: none"> * Frame system * Roll ups * Banner frontlit * Backdrops * Exhibition & events
Weight	260 GSM	DIN EN ISO 2286-2, ASTM D751		
Yarn Specs	FDY 75D/24F	DIN EN ISO 2060, ASTM D1907		
Weave Method	Warp-Knitted 2 bar			
Shrinkage	≤2%	190°C, 1min		
Stretch	Warp: ≤2% Weft: ≤2%		<p>DESCRIPTION: This product is with a black coating on the back for good opaque. No curling edge, good flatness and heavy weight. It is ideal for hanging advertisements. It is a fabric for replacing the display stand.</p>	
Flame Retardant	B1, M1	DIN 4102-1, NFPA701 TEST1		
Standard Width	1.60/2.50 /3.20 M	DIN EN ISO 3759		
Standard Length	50 / 100 M	DIN EN ISO 3759		
Compatible Inks	Eco-Solvent/UV/LATEX/Screen Printing			

Note: For all technical data is a valid tolerance of 5%. We reserve the right for technical modifications. All above information shall only used as a guide. Buyers shall independently test and determine the products suitability.