



Printing & Imaging

Technical Data Sheet

Evolution Premium Coated Paper 140gr

Product specifications

Product:	MH 1484	Unit	Standard
Basic weight	136 ± 13	g/m ²	ISO 536
Paper thickness	167 ± 7	µm	ISO 534
Opacity	95 ± 2	%	DIN 53146
Stiffness md	19 ± 4	mN	ISO 2493
Stiffness cd	10 ± 3	mN	ISO 2493
Smoothness	45 ± 20	s (Bekk)	ISO 5627
CIE Whiteness	155 ± 5	%	ISO 11475
Shade L*	97 ± 2		
a*	3.7 ± 1		
b*	-14.5 ± 2		

Lamination: Cold: Yes

Hot: Yes

Processing: Best printing results occur in a standard climate of 23°C and 50% relative humidity. For problem-free running, always store the printing medium in the original packaging and protect it from direct sunlight and moisture.

Suit for:

- ☐ Solvent inkjet
- ☐ Eco solvent inkjet
- ☐ Latex
- ☐ Cold over laminating
- ☐ UV curable
- ☒ Water based inkjet
- ☐ Screen printing
- ☐ Die Sublimation

Common Applications

- Art Prints, Posters
- Point of sales
- Indoor advertising